



## INSTALLATION MANUAL



MADE IN CANADA

### DISCLAIMER

GreenLane Accessories is a division of Western Edison Manufacturing Corp. All of our products are designed for off-road use. Modify your vehicle at your own risk. By choosing to use our products you take full responsibility and liability for any resulting damages to persons or property. Designs are subject to change without notice. Your safety, and the safety of others is very important. CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE. READ AND UNDERSTAND ALL SAFETY PRECAUTIONS AND OPERATING INSTRUCTIONS BEFORE INSTALLING AND OPERATING THIS PRODUCT.

### PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF WESTERN EDISON MANUFACTURING CORP. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF WESTERN EDISON MANUFACTURING CORP IS PROHIBITED.

### DESCRIPTION:

**5th GEN 4RUNNER FRONT  
SKID PLATE**

### COMPATIBLE WITH:

**2010+ TOYOTA 4RUNNER**

### DATE UPDATED:

**OCTOBER 2020**



# TOYOTA 4RUNNER FRONT SKID PLATE INSTALLATION

APPLICATION: 2010+ TOYOTA 4RUNNER

## PARTS LIST

GREENLANE SKID PLATE	1
M8-1.25 x 25mm BOLT	4
1/4" FLAT WASHER	4
5/16-18 X 5/8" BOLT	3

## TOOLS REQUIRED

METRIC SOCKET SET

ALLEN KEYS

FLATHEAD SCREW DRIVER

## TORQUE SPECS

THREAD SIZE	HEX BOLT HEAD	TORQUE
6mm	10mm	8 ft/lb
8mm	12 or 13 mm	18 ft/lb
10mm	17mm	23 ft/lb
12mm	19mm	50 ft/lb
14mm	22mm	90 ft/lb
1/4 in	7/16 in	12 ft/lb
5/16 in	1/2 in	19 ft/lb
3/8 in	9/16 in	23 ft/lb
1/2 in	3/4 in	90 ft/lb

1. Remove 2 bolts using a 10mm socket. Remove plastic clip in center. These will not be reused.



2. Remove factory skid plates by removing the 4 bolts from the front skid plate, and 4 bolts from the rear skid plate if applicable, using a 12mm socket (13mm socket if you have aftermarket hardware from a differential drop kit). You will not reuse this hardware OR the 1/2" spacers from the drop kit if applicable.



Picture 2.A



Picture 2.B

3. Install new skid plate using 4 of the supplied 13mm bolts and tighten as per torque specs.



**INSTALL COMPLETE**